



SAFETY TIPS

Machinery Hazards

- All washing machines, extractors, and drying tumblers should have a substantial cover over the openings.
- Machines should be equipped with interlock devices that shut the machine off when the door is opened.
- All in-running nip points or rolls should be equipped with a barrier guard.
- Ironing presses and other finishing machinery should be so designed as to prevent the operator or other person from being caught between the ironing surfaces.

Note: For California dry cleaning operations, more specific material and regulations are contained in the Cal OSHA general industry safety orders, sections 4479 ? 4494. California safety regulations also require that dry cleaning operations in that state have a comprehensive injury and illness prevention program. For questions about safety and health practices in dry cleaning operations, please contact your local Zenith branch office for further information.

Zenith provides workplace safety resources at: TheZenith.com[®]

Zenith Insurance Company/ ZNAT Insurance Company. 21255 Califa Street. Woodland Hills, CA 91367 ©2010 Zenith Insurance Company. All Rights Reserved. @Zenith, TheZenith and TheZenith.com are registered US service marks. Zenith Insurance Company (Zenith) assists employers in evaluating workplace safety exposures. Surveys and related services may not reveal every hazard, exposure and/or violation of safety practices. Inspections by Zenith do not result in any warranty that the workplace, operations, machinery, appliances or equipment are safe or in compliance with applicable regulations. Any recommendations and related services are not and should not be construed as legal advice or be used as a substitute for legal advice. Employee protection is ultimately the responsibility of the employer. Policy coverage is not contingent upon the provision, efficacy or sufficiency of these services.